

CUTGRIP

PRODUCT DESCRIPTION : *CUTGRIP is a two pack solvent free Epoxy Resin System containing adhesion promoters.*

RECOMMENDED USES : *Bonding of ceramic tiles to steel surfaces. Grouting of bolts in horizontal grouting applications. Repairing of cracks in walls.*

TECHNICAL INFORMATION

COLOUR : *off-white*

SOLIDS (% BY VOLUME) : *100*

SPECIFIC GRAVITY : *1.5*

POT LIFE : *40 mins @ 25*

GEL TIME : *4 hrs @ 25°C*

SPREADING RATE : *1.1m² per litre @ 1mm
(1kg - ,6m² @ 1mm)*

APPLICATION DATA

APPLICATION METHOD : *Trowel or by hand*

MIX RATIO : *1 part resin by weight or volume
1 part hardener*

WORKING TIME : *40 min @ 25°C*

SURFACE PREPARATION : *Shot blast metal to SA 2½ standards. Surfaces can be cleaned and roughened with a grinder.*

APPLICATION CONDITIONS : *Surface must be dry. Temperature of the substrate must be minimum of 6°C. Good ventilation is necessary when working in confined areas.*

CURING TIME : *Curing times are related to substrate and ambient air temperatures. Curing will be faster at higher temperatures and slower at lower temperatures.*

<u>TEMPERATURE</u>	<u>CURE</u>
15°C	8 hrs
25°C	4 hrs
35°C	2 hrs

STORAGE AND PACKAGING : *The product must be stored at 15°C - 30°C in dry conditions. Keep containers sealed tightly*

PACKAGING : *4kg Kit (2kg Resin / 2kg Hardener)
10kg Kit (5kg Resin / 5kg Hardener)*

HEALTH AND SAFETY : *Spillage on skin can be washed with soap and water. Eyes should be flushed with water immediately and medical advice sought immediately.*

DISCLAIMER: *The information given on this data sheet is given to the best of our knowledge based on laboratory tests and practical experience. However as the product is used under conditions beyond our control we cannot guarantee anything but the quality of the product. We reserve the right to change the given data without notice.*



PRODUCTS (Pty) Ltd

4 BARIUM STREET, ALRODE EXT. 7, P.O. BOX 123920, ALRODE 1451
TEL: (011) 908-3406/7 FAX: (011) 908-2022/ 864-5386